



Composizione / Composition:

100% POLIESTERE / POLYESTER

CON TRATTAMENTO FR / WITH FR BACKING

Altezza / Width: 144 cm. / 56 inches / $\pm 3\%$

Peso / Weight: 800 gr. / MTL / $\pm 5\%$

Resistenza al fuoco / Flame retardancy:

✓ EN 1021/ 1 (cigarette) - 2 (match)

✓ BS 5852, 1 / 2

□ BS 5852 (CRIB 5)

✓ UNI 9175, classe 1 IM

✓ CAL TB 117

✓ NFPA 260

✓ IMO 2010 FTP part 8

Resistenza all'abrasione / Abrasion resistance:

✓ ISO 12947-2 / >80.000 cicli / rubs martindale

✓ ASTM D4157 / >80.000 cicli / rubs martindale

Resistenza alla luce / Light fastness:

✓ ISO 105 - B02 / $\geq 4-5$ (scale 1-8)

✓ AATCC 16.3 / (40 afu) / $\geq 3-4$ (scale 1-5)

Pilling / Pilling:

✓ ISO 12945 / ≥ 4 (scale 1-5)

Solidità allo sfregamento / Colorfastness to crocking:

✓ ISO 105 x 12 / dry $\geq 4-5$ / wet 4 (scale 1-5)

✓ AATCC8 / dry $\geq 4-5$ / wet $\geq 3-4$ (scale 1-5)

Solidità all'acqua / Colorfastness to water:

□ ISO 105 - E03 / (scale 1-5)

Solidità all'acqua marina / Colorfastness to sea water:

□ ISO 105 - E02 / (scale 1-5)

Resistenza al taglio / Seam slippage:

✓ ISO 13936 - 2 / warp 4,00 mm. / weft 4,00 mm.

✓ ASTM D4034 / ≥ 80 lbs.

Manutenzione / Care : RIF. ISO 3758



I rilievi effettuati in laboratorio si intendono sempre indicativi e si riferiscono ai campioni da noi testati / The measurements carried out in the laboratory are always indicative and refer to the samples we tested.



Qubo contract, Italia
Made in E.U.

www.qubcontract.it
e-mail: qubo@qubcontract.it