

ponza - salina - filicudi

upholstery

27

OUTDOOR / FLAME RETARDANT

high performance fabrics



IMO



IGNIFUGO
Flame proof



RICICLABILE
Recyclable



RESISTENTE RAGGI UV
UV Resistant



ANTIMACCHIA
Dirt repellent



ANTIPILLING
No pilling



ANTIBATTERICO
Anti mite



ANTIMUFFA
Anti mould

Composizione / Composition:

ponza

95% POLIPROPILENE / POLYPROPYLENE

5% POLIESTERE / POLYESTER

salina

65% POLIPROPILENE / POLYPROPYLENE

35% POLIESTERE / POLYESTER

filicudi

63% POLIPROPILENE / POLYPROPYLENE

37% POLIESTERE / POLYESTER

Altezza / Width: 140 cm. / 55 inches / \pm 3%

Peso / Weight: **ponza** 720 gr. / MTL / \pm 5%

salina 620 gr. / MTL / \pm 5%

filicudi 650 gr. / MTL / \pm 5%

Resistenza al fuoco / Flame retardancy:

✓ EN 1021/1 (cigarette) - 2 (match)

✓ BS 5852-1 (cigarette) - (match)

□ BS 5852 (CRIB 5)

✓ UNI 9175, classe 1 IM

✓ CAL TB 117

✓ NFPA 260

✓ IMO 2010 FTP part 8

Resistenza all'abrasione / Abrasion resistance:

✓ ISO 12947-2 / 50.000 cicli /rubs martindale

✓ ASTM D4157 / \geq 80.000 cicli /rubs

Resistenza alla luce / Fastness to light:

✓ ISO 105 - B02 / \geq 6-7 (scale 1-8)

✓ AATCC 16.3 / (40 afu) / 5 (scale 1-5)

Pilling / Pilling:

✓ ISO 12945 / 4 (scale 1-5)

Solidità allo sfregamento / Colorfastness to crocking:

✓ ISO 105 x 12 / dry \geq 4-5 / wet \geq 4 (scale 1-5)

✓ AATCC8 / dry \geq 4-5 / wet \geq 4 (scale 1-5)

Solidità all'acqua / Colorfastness to water:

✓ ISO 105 - E03 / 5 (scale 1-5)

Solidità all'acqua marina / Colorfastness to sea water:

✓ ISO 105 - E02 / 5 (scale 1-5)

Resistenza allo scorrimento delle cuciture / Seam slippage:

✓ ISO 13936 - 2 / warp \leq 6,00 mm. / weft \leq 5,00 mm.

✓ ASTM D4034 / \geq 50 lbs.

Manutenzione / Care : RIF. ISO 3758



I rilievi effettuati in laboratorio si intendono sempre indicativi e si riferiscono ai campioni da noi testati / The measurements carried out in the laboratory are always indicative and refer to the samples we tested.



ponza



salina



filicudi

Qubo contract, Italia
Made in E.U.

www.qubocontract.it
qubo@qubocontract.it