



## Composizione / Composition:

80% LANA / WOOL

20% POLIAMMIDICA / POLYAMIDE

**Altezza / Width:** 140 cm. / 55 inches /  $\pm 3\%$

**Peso / Weight:** 600 gr. / MTL /  $\pm 5\%$

## Resistenza al fuoco / Flame retardancy:

✓ EN 1021/ 1 (cigarette) - 2 (match)

✓ BS 5852, 1 / 2

□ BS 5852 (CRIB 5)

✓ UNI 9175, classe 1 IM

✓ CAL TB 117

✓ NFPA 260

✓ IMO 2010 FTP part 8

## Resistenza all'abrasione / Abrasion resistance:

✓ ISO 12947-2 / 60.000 cicli / rubs martindale

✓ ASTM D4157-02 / 60.000 cicli / rubs martindale

## Resistenza alla luce / Light fastness:

✓ ISO 105 - B02 /  $\geq 4/5$  (scale 1-8)

✓ AATCC 16.3 /  $\geq 4/5$  (40 afu) / (scale 1-5)

## Pilling / Pilling:

✓ ISO 12945-2 /  $\geq 4$  (scale 1-5)

## Solidità allo sfregamento / Colorfastness to crocking:

✓ ISO 105-X12 / dry  $\geq 4/5$  / wet  $\geq 3/4$  (scale 1-5)

□ AATCC8 / dry  $\geq 4/5$  / wet  $\geq 3/4$  (scale 1-5)

## Solidità all'acqua / Colorfastness to water:

□ ISO 105 - E03 / (scale 1-5)

## Solidità all'acqua marina / Colorfastness to sea water:

□ ISO 105 - E02 / (scale 1-5)

## Resistenza al taglio / Seam slippage:

✓ ISO 13936-2 / warp  $\leq 4,00$  mm. / weft  $\leq 5,00$  mm.

✓ ASTM D434 / warp  $\geq 80$  lbs / weft  $\geq 60$  lbs.

## Manutenzione / Care : RIF. ISO 3758



I rilievi effettuati in laboratorio si intendono sempre indicativi e si riferiscono ai campioni da noi testati / The measurements carried out in the laboratory are always indicative and refer to the samples we tested.



Qubo contract, Italia  
Made in E.U.

www.qubocontract.it  
e-mail: qubo@qubocontract.it