

FLAME RETARDANT

high performance fabrics



IMO/MED
Certified



IGNIFUGO
Flame proof

Composizione / Composition:

100% TREVIRA CS / TREVIRA CS

Altezza / Width: 140 cm. / 55 inches / ± 3%

Peso / Weight: 580 gr. / MTL / ± 5%

Resistenza al fuoco / Flame retardancy:

- EN 1021/ 1 (cigarette) / 2 (match)
- BS 5852-1:1979 0 (cigarette) / 1 (match)
- BS 5852 (CRIB 5)
- UNI 9175, classe 1 IM
- CAL TB 117
- NFPA 260
- IMO 2010 FTP part 8

Resistenza all'abrasione / Abrasion resistance:

- ISO 12947-2 (Martindale) 150.000 rubs
- ASTM D4157 (Wyzenbeek) 100.000 double rubs

Resistenza alla luce / Light fastness:

- ISO 105 - B02 / ≥5 (scale 1-8)
- AATCC 16.3 / (40 afu) / ≥4 (scale 1-5)

Pilling / Pilling:

- ISO 12945-2 / ≥5 (scale 1-5)

Solidità allo sfregamento / Colorfastness to crocking:

- ISO 105 x 12 / dry ≥4-5 / wet ≥4 (scale 1-5)
- AATCC8 / dry ≥4-5 / wet ≥4 (scale 1-5)

Solidità all'acqua / Colorfastness to water:

- ISO 105 - E03 / (scale 1-5)

Solidità all'acqua marina / Colorfastness to sea water:

- ISO 105 - E02 / (scale 1-5)

Resistenza al taglio / Seam slippage:

- ISO 13936 - 2 / warp ≤3,00 mm. / weft ≤3,00 mm.
- ASTM D4034 / ≥80 lbs.

Manutenzione / Care : RIF. ISO 3758



I rilievi effettuati in laboratorio si intendono sempre indicativi e si riferiscono ai campioni da noi testati / The measurements carried out in the laboratory are always indicative and refer to the samples we tested.



Qubo contract, Italia
Made in E.U.

www.qubocontract.it
e-mail: qubo@qubocontract.it