

FLAME RETARDANT

high performance fabrics

**Composizione / Composition:**

100% POLIESTERE FR / POLYESTER FR

Altezza / Width: 140 cm. / 55 inches / $\pm 3\%$ **Peso / Weight:** 750 gr. / MTL / $\pm 8\%$ **Resistenza al fuoco / Flame retardancy:**

- ✓ EN 1021/ 1(cigarette) / 2(match)
- ✓ BS 5852-1:1979 0(cigarette) / 1(match)
- ✓ BS 5852 (CRIB 5)
- ✓ UNI 9175, classe 1 IM
- ✓ CAL TB 117
- ✓ NFPA 260
- ✓ IMO 2010 FTP part 8

Resistenza all'abrasione / Abrasion resistance:

- ✓ ISO 12947-2 (Martindale) 100.000 rubs
- ✓ ASTM D4157 (Wyzenbeek) 80.000 double rubs

Resistenza alla luce / Light fastness:

- ✓ ISO 105 - B02 / ≥ 5 (scale 1-8)
- ✓ AATCC 16.3 / (40 afu) / ≥ 4 (scale 1-5)

Pilling / Pilling:

- ✓ ISO 12945-2 / $\geq 3/4$ (scale 1-5)

Solidità allo sfregamento / Colorfastness to crocking:

- ✓ ISO 105 x 12 / dry 4-5 / wet 4-5 (scale 1-5)
- AATCC8 / dry / wet (scale 1-5)

Solidità all'acqua / Colorfastness to water:

- ISO 105 - E03 / (scale 1-5)

Solidità all'acqua marina / Colorfastness to sea water:

- ISO 105 - E02 / (scale 1-5)

Resistenza al taglio / Seam slippage:

- ✓ ISO 13936 - 2 / warp 3,00 mm. / weft 3,00 mm.
- ASTM D4034 / lbs.

Manutenzione / Care : RIF ISO 3758

I rilievi effettuati in laboratorio si intendono sempre indicativi e si riferiscono ai campioni da noi testati / The measurements carried out in the laboratory are always indicative and refer to the samples we tested.



Qubo contract, Italia
Made in E.U.

www.qubocontract.it
e-mail: qubo@qubocontract.it